METHOD AND APPARATUS FOR
AUTHENTICATED DIAL-UP ACCESS TO
COMMAND CONTROLLABLE EQUIPMENT

5   **TECHNICAL FIELD**

The present invention relates generally to security and the control of access to equipment through a dial-up connection and, in particular, to methods and apparatus for controlling access to command controllable

10 computerized equipment accessed through a transceiver connected to a dial-up line.

BACKGROUND OF THE INVENTION

Decentralization of service provision is a

15 rapidly developing trend in the service industry. Two simple examples of services provided in a decentralized manner are: the remote maintenance of computerized equipment and access to dial-up services such as banking services. This trend is fuelled by the continuing

20 miniaturization of computing equipment, the exponential increase in processing power of computing equipment and the convenience of providing services at a customer's premises. However, there is a cost associated with the convenience afforded by providing decentralized services.

25 Access to computerized equipment is frequently accomplished using a dial-up connection to a transceiver, such as a modem. This arrangement enables maintenance of the computerized equipment without the expense of dispatching a maintenance person to the site. The

30 enablement of such access, however, exposes the computerized equipment to attacks from unauthorized

- 1 -

persons who accidentally or illegally obtain the dial-up address of the transceiver. Such vulnerability is of significant concern to service providers and has curtailed the development and deployment of decentralized

5   service offerings. There therefore exists a need for a transceiver that enables control over access to computerized equipment that may be accessed through a dial-up connection.

Another attempted solution to the problem is

10   described in United States Patent No. 5,724,426 to Rosenow et al., which issued on March 3, 1998. Rosenow discloses means for controlling access to computer system resources which enable each new session to employ different encryption keys derived from multiple random

15   numbers and multiple hidden algorithms without transmitting the keys across a communication line. Although this system also has merit, it does not provide an optimal solution for the need to enforce control over access to remote computerized equipment because it

20   assumes a central access control system that employs a dedicated parallel control network, such as a LAN, to centrally manage access control tables of an access-controlled system of resources.

There therefore exists a need for a method and

25   apparatus enabling control over secure access to command controllable computerized equipment. The method and apparatus preferably provide user authentication, access control and optimal transaction records.

OBJECTS OF THE INVENTION

It is an object of the invention to provide authenticated access to command controllable computerized equipment.

5 It is another object of the invention to provide a secure access transceiver enabled to authenticate a caller.

It is another object of the invention to provide a secure access transceiver connected to command 10 controllable computerized equipment, the secure access transceiver being enabled to permit data to pass through upon establishing an authenticated connection and otherwise to prevent data from passing through.

It is another object of the invention to 15 provide enforcement of network-centric control of authenticated access to command controllable computerized equipment.

It is another object of the invention to provide an authentication process in which a user 20 connecting to a secure access transceiver is authenticated as part of a handshake sequence.

It is another object of the invention to provide network-centric distribution of authentication information consisting of electronic access keys.

25 It is another object of the invention to provide a secure service transceiver enabled to be associated on a one-to-one basis with a service console.

It is another object of the invention to provide a secure service transceiver enabled to be 30 associated with a pool of secure service transceivers; the pool of secure service transceivers being associated

with a service center which serves as a service point for remote equipment.

It is another object of the invention to provided a secure access controller enabled to authenticate a caller, the access controller being positioned between a modem and computerized equipment to be accessed through a dial-up connection.

It is another object of the invention to provide a secure access controller connected to command controllable computerized equipment, the secure access controller being enabled to permit data to pass through the secure access controller upon establishing an authenticity of a service point and to prevent data from passing through the secure access controller otherwise.

It is yet another object of the invention to provide an authentication process in which a user connecting to a secure access controller from a service point using an access transceiver is authenticated following a link establishing process.

SUMMARY OF THE INVENTION

According to one aspect of the invention, a secure access transceiver is provided for enforcing authenticated access to command controllable computerized equipment. The secure access transceiver authenticates an entity seeking access to the computerized equipment from a remote service point upon detection of a carrier signal during an initial handshake sequence. A data port on the secure access transceiver used to deliver data to the command controllable computerized equipment is enabled only on authentication of the entity seeking

access to the computerized equipment and the data port is kept disabled otherwise, preventing data transfer through the secure access transceiver unless an authenticated connection is established.

5   According to another aspect of the invention, a method of providing authenticated access to command controllable equipment connected to a secure access transceiver in response to a service access request from an entity at a remote point is provided. An initial
10   handshake sequence is performed. The handshake sequence is interrupted upon detection of a carrier signal to perform an authentication process. As part of the authentication process, authentication information is received from the entity at the remote point and is
15   validated. Upon successful authentication, a data port is enabled for a duration of a service session permitting data to pass through to the computerized equipment, the data being otherwise prevented from passing through the secure access transceiver to the command controllable
20   equipment.

     According to another aspect of the invention, a method of enforcing network-centric control over access to a group of command controllable computerized equipment units accessed through secure access transceivers
25   requires a sequence of authentication steps. A service project is defined and stored along with project parameters at a service co-ordination center. A user is pre-authenticated to an authentication server maintained by the service co-ordination center. The project is
30   assigned to at least one user by issuing an electronic access key to the user. A corresponding electronic

access key is stored on the authentication server. The
secure access transceiver associated with the command
controllable computerized equipment to be serviced is
provided with a corresponding electronic access key. The
5   electronic access key is used to authenticate the user
when the user requests access to the computerized
equipment from a remote service point.

According to another aspect of the invention, a
secure access controller is provided for enforcing
10   authenticated access to command controllable computerized
equipment. The secure access controller authenticates an
entity seeking access to the computerized equipment from
a remote service point upon establishing a link. A data
port on the secure access controller for delivering data
15   to the command controllable computerized equipment is
enabled only on authentication of the entity seeking
access to the computerized equipment and the data port is
disabled otherwise, preventing data transfer through the
secure access controller.

20   According to another aspect of the invention, a
method of providing authenticated access to command
controllable equipment connected to a secure access
controller in response to a service access request is
provided. An authentication process is performed upon
25   establishing a link. As a part of the authentication
process, authentication information is received from the
remote point. Upon successful authentication, a data
port is enabled for a duration of a service session
permitting data to pass through the secure access
30   controller to the computerized equipment, and the data is

otherwise prevented from passing through the secure access controller to the command controllable equipment.

According to yet another aspect of the invention, there is provided a method of enforcing network centric control over access to a group of command controllable computerized equipment units accessed through secure access controllers. A service project is defined and stored along with project parameters at a service co-ordination center. A user is pre-authenticated to an authentication server maintained by the service co-ordination center. The project is assigned to at least one user; as part of the assignment an electronic access key is issued to the user. A corresponding electronic access key is stored on the authentication server. The secure access controller associated with the command controllable computerized equipment is provided with a corresponding electronic access key in order to enforce secure access to the computerized equipment.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described by way of example only, and with reference to the accompanying drawings, in which:

FIG. 1 is a connection diagram showing a secure access transceiver with an integrated secure access controller providing authentication checks and enabling access to an access port of a telecommunications switch;

FIG. 2 is a connection diagram showing a transceiver connected to a secure access controller which

provides authentication and access to a telecommunications switch;

FIG. 3 is a schematic diagram showing the relationships between a service point, equipped with a secure service transceiver, a service co-ordination center and secure access transceivers connected to command controllable computing equipment such as a telecommunications switch;

FIG. 4 is a schematic diagram showing the relationships between a stand alone user equipped with a secure service transceiver and an authentication server;

FIG. 5 is a schematic diagram showing the relationships between users associated with a service center which includes a pool of secure service transceivers, and an authentication server;

FIG. 6 is a schematic diagram showing the relationships between a service point equipped with a service transceiver, a co-ordination center, access transceivers and secure access controllers connected to command controllable computing equipment such as a telecommunications switch;

FIG. 7 is a schematic diagram showing the relationships between a stand-alone user equipped with a service transceiver and an authentication server;

FIG. 8 is a schematic diagram showing the relationships between users associated with a service center having a pool of service transceivers, and an authentication server;

FIG. 9 is a flow diagram showing the details of a handshake sequence ending in authentication of a remote service point as implemented on secure transceivers;

FIG. 10 is a flow diagram showing a process by which a secure access transceiver validates a remote calling transceiver;

FIG. 11 is a flow diagram showing a process by which a remote calling transceiver validates the secure access transceiver;

FIG. 12 is a flow diagram showing the initiation of a service call from a workstation associated with a service center equipped with a pool of secure service transceivers;

FIG. 13 is a flow diagram showing the details of a link establishing process in which a secure access controller authenticates a remote service point;

FIG. 14 is a flow diagram showing a process by which a secure access controller validates a calling entity;

FIG. 15 is a flow diagram showing a process by which a valid link is established between a remote point and secure access controller after the remote point validates the secure access controller;

FIG. 16 is a flow diagram showing the details of the initiation of a service call from a workstation associated with a service center equipped with a pool of service transceivers in order to connect to a secure access controller through an access transceiver;

FIG. 17 is a flow diagram showing a process by which a service access request is initiated;

FIG. 18 is a flow diagram showing a process by which secure access equipment is updated with new access keys;

FIG. 19 is a flow diagram showing a process for placing a service call to establish a service session with command controllable computerized equipment; and

FIG. 20 is a flow diagram showing a process by which a control point and secure access equipment activate administration mode.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In accordance with a first embodiment of the invention, there is provided a secure access transceiver for secure authenticated access to computerized equipment. The secure access transceiver performs all the functions of a standard modem if a remote user successfully authenticates as a trusted authorized user having access to the computerized equipment. Otherwise, a communications port of the transceiver connected to the computer equipment is disabled to ensure that access to the equipment is unconditionally denied. This preferred implementation is shown in FIG. 1 in which a telecommunications switch 100 having at least an access port 102 is connected to the secure access transceiver 104. The secure access transceiver 104 has an integrated secure access controller. According to this implementation, the telecommunications switch 100 is accessed for systems maintenance from the public switched telephone network 106 through the secure access transceiver 104.

In accordance with a second embodiment of the invention, access to the computerized equipment is controlled by a secure access controller connected to a link between a transceiver and the computerized

equipment. The access controller authenticates a remote user after the transceiver has established a link with the remote user. If the user is authenticated as trusted and authorized for access, the access controller passes

5   data from the remote user to the computerized equipment, and vice versa. Otherwise, all communications between the remote user and the computerized equipment are disabled. This embodiment of the invention is shown in FIG. 2. A telecommunications switch 100 having at least

10 an access port 102 is accessed through the secure access controller 108 for systems maintenance purposes. The secure access controller 108 is further connected to the transceiver 110. The telecommunications switch 100 is serviced from the public switch telephone network 106

15 through the transceiver 110 and the secure access controller 108.

Each embodiment of the invention may operate as a stand-alone unit or be controlled by a central administration authority which administers access to the

20 computerized equipment.

FIG. 3 shows a schematic diagram representing a network configuration as it applies to maintenance of distributed telephone circuit switching equipment using access equipment according to a preferred embodiment of

25 the invention. A command controllable computerized equipment, for example, a telecommunications switch 100 can be maintained and serviced through access ports 102. At least one secure access transceiver 104, from a secure access transceiver pool 112, is connected to one of the

30 access ports 102 in order to provide secure and authenticated access to the telecommunications switch 100

- 11 -

for maintenance purposes. The secure access transceiver 104 has a data port (not shown) through which it connects to one of the access ports 102 of the telecommunications switch 100. The telecommunications

5 switch 100 is serviced from a service point 114 located remotely with respect to the telecommunications switch 100.

In this example, a stand-alone user 116 using a portable computer 118 seeks access to the

10 telecommunications switch 100. The stand-alone user 116 uses a secure service transceiver 120 to access the telecommunications switch 100. The secure service transceiver 120 has a data port (not shown) used to connect the secure service transceiver 120 to the

15 portable computer 118. Associated with the user 116 is a smart card 122 which contains authentication information.

The access to the telecommunications switch 100 is managed by a service co-ordination center 124. To enforce control over secure access to the

20 telecommunications switch 100, the service co-ordination center 124 has associated with it an authentication server 126. The authentication server controls access to selected equipment by permitting only authorized personnel to access the equipment, as will be described

25 below with reference to FIG. 17. The stand-alone user 116 uses the secure service transceiver 120 to connect to the authentication server 126 of the service co-ordination center 124, shown as link A, through telecommunications switch 128, the public switched

30 telephone network (PSTN) 106 and telecommunications switch 130. If the stand-alone user is successfully

validated as an authorized person, the service co-ordination center 124 connects to the secure access transceiver 104, shown as link B, through telecommunications switch 130 and the PSTN 106 to update equipment memory to permit the stand-alone user to access the equipment as will be explained below in detail. In order for the user 116 to service the telecommunications switch 100, shown as link C, the user 116 uses the secure service transceiver 120 to connect through telecommunications switch 128, the PSTN 106, the telecommunications switch 100, the secure access transceiver 104 and the access ports 102 of the telecommunications switch 100. During the process of establishing a service link with the telecommunications switch 100, the stand-alone user 116 is validated as an authorized person in a process described below with reference to FIGS. 9 to 12.

FIGs. 4 and 5 are schematic diagrams showing the relationship between service points 114, 140, as explained above, the stand-alone user 116 is equipped with the portable computer 118 and the secure service transceiver 120. The stand-alone user 116 accesses the co-ordination center 124 in order to request access to service command controllable computerized equipment through the public switched telecommunications network 106. FIG. 5 shows another service point from which users 132 work from service center workstations using secure service transceivers 134 which are components of a secure service transceiver pool 136.

FIG. 6 is a connection diagram showing a network configured similarly to the network shown in

FIG. 3 except that access to the telecommunications switch 100 is accomplished using standard transceivers and access is controlled by secure access controllers in accordance with the invention. The telecommunications

5 switch 100 is serviced through access ports 102. At least one secure access controller 108, connected on a one-to-one basis with an access transceiver 110, provides secure authenticated access to the telecommunications switch 100 for purposes of maintaining and servicing the

10 telecommunications switch 100. Access transceiver 110 may be a part of a pool of access transceivers 142. The access transceiver 110 has a data port (not shown) with which it connects to one of the secure access controllers 108. The secure access controller 108 has

15 two data ports (not shown) through which it connects on one side to the access transceiver 110 and on the other side to an access port 102 of the telecommunications switch 100. The telecommunications switch 100 is serviced from a service point 114 located remotely with

20 respect to the telecommunications switch 100.

Using the access equipment shown in FIG. 6, a stand-alone user 116, using a portable computer 118 services the telecommunications switch 100. In order for the stand-alone user 116 to access the telecommunications

25 switch 100, a service transceiver 144 is employed. Preferably, the user 116, is issued a smart card 122 which contains authentication information, although other authentication schemes may be used for the same purpose. Network-centric control over access to the

30 telecommunications switches to be serviced is provided by the service co-ordination center 124.

FIGs. 7 and 8 show two types of service points, one consisting of a stand-alone user with a portable computer and the other consisting of a user at a service center. The user equipment is distinguished from the user equipment described in FIGs. 4 and 5 because standard transceivers 144, 146 are used at the remote service points.

FIG. 9 shows a link-establishing sequence performed by the secure access transceivers in accordance with the invention as an attempt is made to access computerized equipment connected to the secure access transceiver.

Upon power-up, the secure access transceiver 104 (FIG. 3) performs a start-up sequence (step 200) during part of which the communications port of the secure access transceiver 104 connected to the command controllable computerized equipment is disabled (step 202). The start-up sequence terminates, leaving the secure access transceiver in a state in which the secure access transceiver 104 is waiting for a ring signal, step 204.

When a call is initiated in step 210, from a remote point, a dialing sequence is performed (step 212). The dialing sequence triggers a link establishing process 211. The detection of the ring signal, at the secure access transceiver 104, in step 214, initiates a corresponding link establishing process 213. Upon detection of the ring signal, the secure access transceiver 104 and the transceiver at the remote point begin a handshake sequence, steps 216 and 218. A successful handshake commencement of the sequence

terminates in both ends detecting a carrier signal, steps 220 and 222, thereby terminating link establishing processes 211 and 213. After the carrier signal is established, the transceiver at the remote point sends authentication information to the secure access transceiver 104 (step 224). The secure access transceiver 104 validates the authentication information in step 226. Failure to detect the carrier signal in step 222 and/or failure to authenticate the remote user at the remote point, in step 226, causes the secure access transceiver 104 to hang up (step 228), and return to a state of waiting for a ring signal, step 204. If authentication of the information received by the secure access transceiver 104 is successful, step 226, the secure access transceiver 104 initiates a cross validation process which commences with a validation of the remote user, in step 230.

FIG. 10 is a flow diagram illustrating an exemplary process by which the secure access transceiver 104 validates the user. The user validation sequence starts when the secure access transceiver generates a random number in step 232. The random number is sent, in a message, to the remote point (step 234). Upon receipt of the message at the remote point, the number is encrypted using an electronic encryption key in step 238. The encrypted number is signed at the remote point with an electronic signature and the encrypted and signed number is sent back to the secure access transceiver 104 in another message (step 240). Upon receipt of this message, the secure access transceiver 104 validates the signature in step 242. If

the signature belongs to an authorized user, the message
is decrypted using a matching electronic decryption key,
step 244.   If the number sent by the secure access
transceiver 104 matches the number received and decrypted

5 by the secure access transceiver 104 (step 246), an
acknowledgement is sent to the remote point (step 248).
If   the   secure   access   transceiver   104   does   not
successfully validate the signature of the received
message (step 242), or the decrypted number does not

10 match the one sent, the secure access transceiver 104
hangs up (step 250) and returns to the state of waiting
for a ring signal (step 204).   Acknowledgement of the
validation of the user (step 252), may optionally
initiate a secure access transceiver validation sequence

15 (step 254) for enhanced security.   The remote point
allows for a reasonable length of time to pass for the
receipt of the message in step 236 and for the receipt of
the acknowledgement in step 252.   After a sufficient
amount of time has elapsed for either of the two events,

20 the remote point hangs up in step 253 and terminates in
step 255.

FIG. 11 shows the secure access transceiver
validation process used for enhanced security.   In order
to validate the secure access transceiver 104, a random

25 number is generated at the remote point in step 256.   The
random   number   is   sent   to   the   secure   access
transceiver 104 in a message, in step 258.   An encryption
of the number using another electronic encryption key is
performed in step 262.   The encrypted number is signed by

30 the   secure   access   transceiver   104   using   another
electronic signature and the encrypted and signed number

- 17 -

is sent to the remote point in a message in step 264. The remote point allows for a reasonable length of time to pass for the receipt of the encrypted and signed message in step 266. After a sufficient amount of time has elapsed the remote point hangs up in step 271, and terminates in step 273. Validation of the secure access transceiver signature is performed in step 266. Upon successful validation of the secure access transceiver's signature key, the message is decrypted using another electronic decryption key in step 268. A comparison is performed between the generated random number and the received number in step 270. Upon successful comparison of the two numbers, an acknowledgement message is sent to the secure access transceiver in step 272. The remote point also hangs up, in step 271, if the comparison of the two numbers is unsuccessful. If the secure access transceiver fails to receive a message from the remote point, in step 260, or if the remote point does not send an acknowledgement message, in step 274, the secure access transceiver 104 hangs up, in step 280, and returns to a state in which it is waiting for a ring signal, step 204. Successful cross-validation leads to establishing a valid link (steps 278 and 276). Upon validating the link, the secure access transceiver 104 enables the communication port connected to the command controllable computerized equipment, in step 282. At the same time, the remote point may also enable its communication port, if it had been previously disabled.

Shown in FIG. 12 are the details of the initiation of a service call by a user 132 from a workstation associated with a pool 136 of secure service

transceivers 146. The procedure is similar to the one
shown in FIG. 9 except for a few preliminary steps. On
placing the service call from the workstation, the first
step is to update, in step 300, a secure service
5   transceiver 134, assigned by a service center access
server 138 to the workstation from the pool 136, with
electronic keys necessary for the authentication and
validation steps. The secure service transceiver 134 in
the pool 136 records the necessary electronic keys in
10   step 302. A call request is placed at the service
workstation, in step 304, in response to which the secure
service transceiver 134 in the pool 136 may disable its
communications port, step 306, and proceeds with the call
and authentication process as previously described in
15   relation to FIG. 9.

    The above described implementation is suitable
for deployment of new services to be offered. For the
case in which the command controllable computerized
equipment with the associated access transceiver are
20   already deployed, replacement of existing access
transceivers with secure access transceivers would not be
a financially viable solution. This is the reason behind
the second embodiment in which in which secure access
controllers are installed between the access transceivers
25   and the command controllable computerized equipment are
already deployed.

    Accordingly, a method of authenticating an
entity seeking access from a remote point to command
controllable computerized equipment through an access
30   transceiver and a secure access controller is shown in
FIG. 13. Upon power-up, the access transceiver goes

through a start-up sequence, step 200. The start-up sequence terminates, leaving the access transceiver in a state in which the access transceiver is waiting for a ring signal, step 204.

5   On placing a call to the access transceiver, step 210 from a remote point, the remote point and the access transceiver go through a process of establishing a communications link, steps 211 and 213, respectively. Upon establishing a communications link, the access

10   transceiver informs the secure access controller of the established communication link by asserting a Data Terminal Ready signal (DTR), step 221.

      Upon power-up of the secure access controller 108 (step 201), the secure access

15   controller 108 disables its communication port connected to the computerized equipment (step 202). The start-up sequence of the secure access controller 108 terminates leaving the secure access controller 108 in a state in which it is waiting for a Data Set Ready (DSR) signal

20   (step 203). Upon detection of the DSR signal, by the secure access controller, in step 203, which is equivalent to detecting the assertion of the DTR set by the access transceiver, the secure access controller 108 asserts its DTR signal in step 225, establishing a link

25   between the access transceiver 110 and the secure access controller 108. Upon establishing the communications link, in step 211, the remote point sends an access certificate, in step 224, to the secure access controller 108. In step 226, the secure access

30   controller 108 validates the access certificate and, upon validation of the access certificate, the secure access

controller 108 initiates a cross validation sequence starting by validating the caller (step 231). Failing to validate the access certificate in step 226, the secure access controller 108 drops its DTR signal in step 227. The access transceiver 110 monitors its DSR input and, if the secure access controller 108 drops its DTR signal, the access transceiver 110, in step 228, hangs up and returns to a state in which it is waiting for a ring (step 204). At the same time, the secure access controller returns to a state in which it is waiting for a DSR signal.

FIGs. 14 and 15 show the details of the cross validation sequence between the remote point in the secure access controller 108. The steps of the cross-validation sequence are similar to the sequence presented above in relation to the preferred embodiment with the distinction that authentication is handled by the remote point and the secure access controller, and the details of establishing the connection are handled by the transceiver at the remote point and the access transceiver, respectively.

FIG. 16 shows the extra details related to placing a service call from a service center workstation. A transceiver 146 from the transceiver pool 136 is selected and remains associated with the service call for the duration of the service session.

All other details are similar to the previous implementation in all respects. In fact, the two implementations presented can co-exist and inter-operate with each other.

Having described the implementation details according to two examples; the secure access transceiver and the secure access controller will be henceforth referred to as secure access equipment.

A preferred implementation of a method for enforcing network-centric control over access to command controllable computerized equipment is shown in FIGs. 17, 18, 19 and 20. FIG. 17 in particular shows the details of a process by which a service access request is initiated. A user who is a member of an authorized community to access telecommunications switches is assigned a project. The user proceeds from a service access request, step 500. The user 116 signs on at a console, such as a portable computer 118 for example, in step 502. Upon successful sign-on, the user requests access to the authentication server 126 by entering relevant information about the user, step 506. The authentication server 126 checks as to whether the user is still a trusted user, step 508. If the user is still a trusted user, the authentication server 126 sends an acknowledgement message to the service point, step 510. On receiving the acknowledgement message, in step 512, the user enters project variables, in step 514. The authentication server 126 checks as to whether the project is a valid project and whether the user is expected to service the telecommunications switch 100 specified by the project, as previously defined in a database at the authentication server, step 516. If the project is valid, the authentication server sends an acknowledge message, in step 518, to the service point. Failing to recognize the user as a trusted user in

step 508 or failing to find a previously defined valid project in the database associated with the user in step 516, the authentication server 126 denies access to the user in step 517. On receiving acknowledgement in step 520, the user requests an electronic access key set, in step 522. The authentication server 126 generates an electronic key set, step 524, and sends the key set to the user, in step 526. The user stores the electronic access key set which is valid for a duration of the service to be performed, or a limited time period thereof.

Following this initiation process, the authentication server 126 proceeds to update the secure access transceiver 104 connected to the telecommunications switch 100 specified by the project, in step 530. Having the electronic access key set, the user proceeds to place a service call to the secure access transceiver 104 and service the telecommunications switch 100 as specified by the project, step 544.

The update process of the secure access transceiver 104 is shown in FIG. 18. The necessary steps involved are: calling, 210, the secure access transceiver 104, step 210; establishing a link, step 211; performing cross validation, step 280, activating administration mode, step 536; cross validating at the administration level, step 280; updating the secure access transceiver, step 540 and ending, step 543, by hanging up, step 542.

The process followed in the course of a service session is shown in FIG. 19. In servicing the telecommunications switch 100 connected to a secure

access transceiver 104 specified by the project, a user follows the following steps: a call is placed to the secure access transceiver 104, step 210; a link is established, step 211; cross validation is performed,

5   step 280, a service session follows in which the telecommunications switch 100 is serviced, step 550, and on completion, the session is terminated, 553, by a hang-up in step 552.

The process by which a control transceiver and

10   secure access equipment activate the administration mode is shown in FIG. 20. On activating administration mode 536, the control transceiver associated with the authentication server 126 sends an administration mode request in step 560. The control transceiver also

15   activates its electronic administration keys and may disable its communication port (steps 564 and 568, respectively). On receiving an administration mode request in step 562, the secure access equipment disables the communication port, activates its electronic

20   administration keys and proceeds to validate the caller as part of the cross validation process (steps 566, 570 and 230, respectively). If the request received in step 562 is not an administration mode request, the secure access equipment checks as to whether the request

25   is a valid request in step 580. If the request is valid, then the secure access equipment proceeds to process the request. If the request is not valid then the secure access equipment hangs up in step 584 terminating the session, step 586.

30   In order to implement network-centric control over access to deployed command controllable computerized

equipment accessed through secure access equipment, functionality is provided on the secure access equipment to enable it to act independently of the co-ordination center. The secure access equipment is provided with

5 electronic memory storage, embedded processing capabilities, absolute time clock, etc. The electronic memory storage is used to store, in a retrievable fashion, authentication information, transaction records and certificate revocation lists.

10 Active certificates corresponding to ongoing service projects are stored in the authentication information portion of the memory storage. The access certificates include the electronic access keys, as mentioned in the above descriptions. These access

15 certificates have a time period of validity which is enforced using the real time clock. Records regarding access to the command controllable computerized equipment through the secure access equipment are kept in the transaction records portion of the memory storage.

20 Invalid certificates are stored in the certificate revocation list portion of the memory storage.

Upon updating the secure access equipment from a control point: new access certificates are stored in the authentication information portion of the memory

25 storage, the transaction records are downloaded and the revocation lists updated. Alternatively the secure access equipment can call the control point to download its transaction records and update its revocation lists either on a specific time cycle or on critical conditions

30 triggered by lengthy transaction records and stale revocation lists. Other situations related to enforcing

secure access to command controllable computerized equipment in which the secure access equipment can call the control point would include numerous repetitive failed access attempts from the same remote point.

5   Having the elements mentioned above different methods known in the art providing different degrees of secure access can be implemented in an actual realisation but still falling within the scope of the invention. For example, as an added level of security, once the service

10   session is established, an encryption key can be generated and used for encrypting the exchanged data over the communications link for the duration of the service session. This encryption key would only be known to the secure access equipment and the service point. Another

15   implementation would have the electronic memory storage, the real time clock and the embedded processor on a smart card associated with the secure access equipment.

          Although the invention has been explained with reference to telephone network equipment, it should be

20   understood by those skilled in the art that the invention is in no way limited to such applications. The apparatus and methods in accordance with the invention may be used to control access to any computerized equipment accessed by a transceiver. For example, the invention may be used

25   to control access to a personal computer, local or wide area network, any other computing machine or computerized equipment having an access port that may be accessed through a transceiver.

          The scope of the invention is therefore

30   intended to be limited solely by the scope of the appended claims.